

Label Information

The Spectrum label presents technical and safety information in an easily understood format. Our technical specialists stay abreast of the latest requirements of the Globally Harmonized System for Classification and Labelling of Chemicals (GHS), as well as the Occupational Safety and Health Administration (OSHA), the Food and Drug Administration (FDA) and other government regulatory agencies in order to ensure compliance, accuracy and concise hazard communication. Below you will find a typical label example for this catalog item.



DANGER

 May be fatal if swallowed and enters airways.

*FIRST AID: IF SWALLOWED:
PImmediately call a POISON CENTER
Or physician. DO NOT induce vomiting.

KEEP FROM CHILDREN

Light Mineral Oil

NF

CAS 8042-47-5

CAUTION: For manufacturing, processing or repacking.

Read and understand the label and Safety Data Sheet (SDS) prior to use.

Chemical Emergency: (800)424-9300

www.SpectrumChemical.com

Viscosity Range: 65-75 SUS @ 100° F DL- α -Tocopherol (Vitamin E) added as a stabilizer.

	Specific Gravity	0.818-0.880
	Viscosity @ 40.0°C	3.0-34.4 mm ² /s
	Acidity	
MAXIMUM LIMITS		
	Readily Carbonizable Substances	To pass test
	Polycyclic Aromatic Hydrocarbons	To pass test
	Solid Paraffin	To pass test
	Sulfur Compounds	
	Elemental Impurities	
	Residual Solvents	To pass test

LIGHT SENSITIVE: Keep tightly closed in light-resistant containers.

FLUSHED WITH NITROGEN

G 14/H7GHS ? Lot No. XQ####

Spectrum Chemical Mfg Corp

Corporate Headquarters: 769 Jersey Ave.

769 Jersey Ave. New Brunswick, NJ 08901

732.214.1300

West Coast Facility: 14422 S. San Pedro St. Gardena, CA 90248

310.516.8000