

Labconco Purifier Horizontal Clean Benches

Description • Horizontal laminar flow

- Supplied HEPA filter is 99.99% efficient on 0.3 micron particles
- Double-gasket, negative pressure HEPA filter leak protection
- ISO Class 5 air (formerly Class 100 per Federal Standard 209E)
- Variable speed, built-in motor/blower(s) with vibration isolation pads
- Differential pressure gauge
- Type 304 brushed stainless steel work surface
- $\frac{1}{4}$ in. thick tempered safety glass side panels with utility ports with iris openings
- UV-resistant, glacier white, powder-coated steel exterior
- Fluorescent lighting
- Front-mounted light and blower switches
- ETL Listing, UL/CSA C22.2 No. 61010-1 conformity
- 115V, 60 Hz, 6A (230 volt, 50/60 Hz models are also available)
- 1 year warranty on parts and service



Options:

- Factory-installed 254 nm UV lamp with UV screen and interlocking safety switch which allows operation only when blower and fluorescent light are off and UV screen is closed, to prevent inadvertent UV exposure while the bench is in operation
- UV lamp has a variable digital timer that provides timed UV light exposure in minutes of 5, 10, 15, 30, 60, 120, 240, and continuous
- UV screen acts as a barrier when the UV light is on and bench is not in use
- IV Bar Kit is an optional accessory; 3, 4, and 5 ft. models require one; 6 ft. models require two (to be ordered separately)

Replacement Prefilters:

- 3 ft. models require two prefilters (Catalog No. 346-14335)
- 4 ft. models require two prefilters (Catalog No. 346-14344)
- 5 ft. models require three prefilters (two of Catalog No. 346-14335 **AND** one of Catalog No. 346-14344)
- 6 ft. models require three prefilters (Catalog No. 346-14344)

Required Accessory:

- Supporting base (available separately, to order please see Labconco Base Stands for Horizontal Clean Benches)

Image(s) are representative of the product group and not necessarily the individual product.

No options of this product are available.