

Labconco Coated Steel Belt Driven Blowers

Description • Specifically designed to meet the demanding day-to-day ventilation requirements for a wide range of hood choices

- Durable and easy to maintain
- Recommended accessory for fume hoods used for low to moderately corrosive applications
- Offered in a broad spectrum of capacities from 175 to 1960 CFM at static pressures to 1.50 in. H₂O
- Explosion-proof models have non-sparking aluminum impellers and UL-listed explosion-proof motors for maximum safety



Both types of Coated Steel Blowers feature:

- Flow-through vent holes and louvers allow for air circulation that cools the motor
- Phenolic coating on impeller and housing is corrosion resistant
- Powder-coated base and weather cover provide long life in extreme weather
- Belt-driven with adjustable sheave saves energy and allows you to fine tune air volumes
- Removable weather cover allows easy access for lubrication and sheave alignment
- Self-adjusting gravity belt tightener ensures consistent performance
- Motor mount keeps the motor in place should the belt ever fail
- Forward curved impellers are balanced to ensure quiet operation and optimum air delivery
- Factory lubricated pillow block bearings reduce maintenance and increase life
- Blowers have low RPM for quiet operation
- Sound levels generally range between 64 and 88 decibels depending on blower size
- Variable exhaust orientation adjusts to eight outlet positions for installation flexibility
- Adjustable discharge direction accommodates auxiliary-air requirements or unusual blower locations
- Ductwork required (not included)

Image(s) are representative of the product group and not necessarily the individual product.

Order	18-Apr-2024 23:18: PM PDT	PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.					
Catalog	Item	Availability	Manufacturer	Mfg. Part #	NDC#	Your Price	Unit
346-16834-EA	Coated Steel Blower, 10 in. inlet, 1/6 HP - 1 ea Standard, 10 in. inlet HP: ¹/₆ Electrical Requirements: 115V, 60 Hz, 4A RPM Range: 529 to 807 Shipping Weight (lbs): 92 For use with: 4 ft. models 	Sign In	Labconco	7068000			EA
346-16837-EA	Explosion Proof Coated Steel Blower, 10 in. inlet, 1/6 HP - 1 ea Explosion Proof, 10 in. inlet HP: ¹/₆ Electrical Requirements: 115V, 60 Hz, 3.15A RPM Range: 529 to 807 Shipping Weight (lbs): 100 For use with: 4 ft. models 		Labconco	7068100			EA

Order	18-Apr-2024 23:18: PM PDT	PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.					
Catalog	Item	Availability	Manufacturer	Mfg. Part #	NDC#	Your Price	Unit
346-16840-EA	Explosion Proof Coated Steel Blower, 10 in. inlet, 1/4 HP - 1 ea Explosion Proof, 10 in. inlet HP: ¹</sub>4</sub> Electrical Requirements: 115V, 60 Hz, 4.5A RPM Range: 752 to 1067 Shipping Weight (lbs): 100 For use with: 6 ft. models 		Labconco	7068300			EA
346-16843-EA	Coated Steel Blower, 10 in. inlet, 1/3 HP - 1 ea Standard, 10 in. inlet HP: ¹</sub>3</sub> Electrical Requirements: 115V, 60 Hz, 6.1A RPM Range: 929 to 1260 Shipping Weight (lbs): 86 		Labconco	7068400			EA
346-16846-EA	Explosion Proof Coated Steel Blower, 10 in. inlet, 1/3 HP - 1 ea Explosion Proof, 10 in. inlet HP: ¹</sub>3</sub> Electrical Requirements: 115V, 60 Hz, 6.4A RPM Range: 929 to 1260 Shipping Weight (lbs): 94 		Labconco	7068500			EA
346-16849-EA	Coated Steel Blower, 10 in. inlet, 1/2 HP - 1 ea Standard, 10 in. inlet HP: ¹</sub>2</sub> Electrical Requirements: 115V, 60 Hz, 8.4A RPM Range: 1073 to 1456 Shipping Weight (lbs): 88 		Labconco	7068600			EA
346-16852-EA	Explosion Proof Coated Steel Blower, 10 in. inlet, 1/2 HP - 1 ea Explosion Proof, 10 in. inlet HP: ¹</sub>2</sub> Electrical Requirements: 115/230V, 60 Hz, 9.0/4.5A RPM Range: 1073 to 1456 Shipping Weight (lbs): 96 		Labconco	7068700			EA
346-16855-EA	Explosion Proof Coated Steel Blower, 12 in. inlet, 1/3 HP - 1 ea Explosion Proof, 12 in. inlet HP: ¹</sub>3</sub> Electrical Requirements: 115V, 60 Hz, 6.4A RPM Range: 373 to 569 Shipping Weight (lbs): 90 		Labconco	7068900			EA
346-16858-EA	Coated Steel Blower, 12 in. inlet, 1/2 HP - 1 ea Standard HP: ¹</sub>2</sub> Electrical Requirements: 115V, 60 Hz, 8.4A RPM Range: 532 to 753 Shipping Weight (lbs): 96 		Labconco	7069000			EA
346-16861-EA	Explosion Proof Coated Steel Blower, 12 in. inlet, 1/2 HP - 1 ea Explosion Proof, 12 in. inlet HP: ¹</sub>2</sub> Electrical Requirements: 115/230V, 60 Hz, 9.0/4.5A RPM Range: 532 to 753 Shipping Weight (lbs): 104 		Labconco	7069100			EA

Order	18-Apr-2024 23:18: PM PDT	PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.					
Catalog	Item	Availability	Manufacturer	Mfg. Part #	NDC#	Your Price	Unit
346-16864-EA	Explosion Proof Coated Steel Blower, 12 in. inlet, 3/4 HP - 1 ea Explosion Proof, 12 in. inlet HP: ³</sub></sub> Electrical Requirements: 115/230V, 60 Hz, 11.4/5.7A RPM Range: 667 to 946 Shipping Weight (lbs): 100 		Labconco	7069300			EA
346-16867-EA	Explosion Proof Coated Steel Blower, 12 in. inlet, 1 HP - 1 ea Explosion Proof, 12 in. inlet HP: 1 Electrical Requirements: 115/230V, 60 Hz, 13.6/6.8A RPM Range: 828 to 1173 Shipping Weight (lbs): 108 		Labconco	7069500			EA
346-16870-EA	Coated Steel Blower, 12 in. inlet, 1-1/2 HP - 1 ea Standard HP: ¹</sub></sub> Electrical Requirements: 115/230V, 60 Hz, 20.4/10.2A RPM Range: 920 to 1303 Shipping Weight (lbs): 114 		Labconco	7069600			EA
346-16873-EA	Explosion Proof Coated Steel Blower, 12 in. inlet, 1-1/2 HP - 1 ea Explosion Proof, 12 in. inlet HP: ¹</sub></sub> Electrical Requirements: 230/460V, 60 Hz, 4.8/2.4A RPM Range: 920 to 1303 Shipping Weight (lbs): 122 		Labconco	7069700			EA
496-21058-EA	Coated Steel Blower, 10 in. inlet, 1/4 HP - 1 ea Standard, 10 in. inlet HP: ¹</sub></sub> Electrical Requirements: 115V, 60 Hz, 4.4A RPM Range: 752 to 1067 Shipping Weight (lbs): 92 For use with: 6 ft. models 		Labconco	7068200			EA
496-21085-EA	Coated Steel Blower, 12 in. inlet, 1/3 HP - 1 ea Standard, 12 in. inlet HP: ¹</sub></sub> Electrical Requirements: 115V, 60 Hz, 6.1A RPM Range: 373 to 569 Shipping Weight (lbs): 90 		Labconco	7068800			EA
496-21103-EA	Coated Steel Blower, 12 in. inlet, 3/4 HP - 1 ea Standard HP: ³</sub></sub> Electrical Requirements: 115/230V, 60 Hz, 11.6/5.8A RPM Range: 667 to 946 Shipping Weight (lbs): 96 		Labconco	7069200			EA
496-21112-EA	Coated Steel Blower, 12 in. inlet, 1 HP - 1 ea Standard HP: 1 Electrical Requirements: 115/230V, 60 Hz, 13.6/6.8A RPM Range: 828 to 1173 Shipping Weight (lbs): 100 		Labconco	7069400			EA
496-48190-EA	Coated Steel Blower, 12 in.,inlet, 2 HP - 1 ea Standard HP: 2 		Labconco	7071900			EA