

Sper Scientific* Advanced Thermocouple Thermometers with RS232 Output Dataloggers



- Description** • These highly accurate thermometers accept any type K thermocouple probes
- Automatically records up to 16,000 data points in the field
 - These data points can later be downloaded to a computer via the meter's RS232 port and the results viewed instantly on the ThermoLog Software which comes with the unit
 - Maximum Interval Setting Time is 60 minutes in Datalogger Mode
 - Fast response time over a wide temperature range and high resolution
 - Advanced features include a large 3 1/2 in. digit LCD, hold, auto power off, min./max./average, and relative temperature functions
 - Handy built in timer for measuring temperature stabilization time and for other applications
 - Meter includes a soft carrying case, RS232 cable (Cat. No. 350-52228), beaded wire probe (Ambient Type K probe, Cat. No. 350-98779), and 9V battery
 - Cat No. 350-52252 includes a NIST traceable certificate of compliance

Specifications:

- Range: -200 to 1370°C (-328 to 2498°F)
- Resolution: 0.1°C (-200 to 800°C), 1°C (800 to 1370°C), 0.1°F (-328 to 1000°F), 1°F (1000 to 2498°F)
- Accuracy: ±(0.1% reading + 0.7°C), ±(0.1% reading + 1.4°F)
- Dimensions: 7 1/4 x 2 1/2 x 1 1/4 in. (184 x 64 x 32 mm)
- Weight: 7.4 oz (210 g)
- 5 year warranty, CE, UL

Image(s) are representative of the product group and not necessarily the individual product.

Order	01-May-2024 14:13: PM PDT		PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.				
Catalog	Item	Availability	Manufacturer	Mfg. Part #	NDC#	Your Price	Unit
350-52249-EA	Advanced Thermocouple Type K Thermometer with RS232 Datalogger - 1 ea Certificate of Compliance: No 	Sign In	Sper Scientific	800008			EA