

Control Company Traceable* Digital Humidity/Temperature/Dew Point Meter

Description • Audible and visual LED alarm may be set to trigger at three different humidity readings (55%, 60% or 65%)

• Solid state sensors deliver response times of less than 30 seconds, °F/°C switchable

• Convenient triple memories recall minimum/maximum readouts for relative humidity, dew point, and temperature

• Simultaneously displays all three current readings

• Always-on feature allows for monitoring conditions all night, over weekends, and for extended time periods

• Oversized display supplies updates once a second

• To assure accuracy an individually serial-numbered Traceable* Certificate is provided from Control Company's ISO/IEC 17025 (1750.01) calibration laboratory accredited by A2LA

• It indicates traceability to standards provided by NIST (National Institute of Standards and Technology)

• Case: durable, chemical and shock-resistant ABS plastic

• Supplied: wall mount, batteries, and Traceable* Certificate



Specifications:

• RH Range: 1 to 99% RH

• RH Accuracy: ±3% mid-range, ±5% elsewhere

• RH Resolution: 0.01

• Probe Type: Internal Sensor

• RH Probe External/Internal?: Internal(Ambient)

• Temperature Range: -10 to 60°C (14 to 140°F)

• Internal Temperature Range: 14 to 140°F (-10 to 60°C)

• Internal Temp Resolution: 0.1°

• LCD Digit Size: 3/4 in

• Dimensions: 2-5/8"x3-7/8"x5/8"

• Weight: 6 ounces

Image(s) are representative of the product group and not necessarily the individual product.

Order	24-Apr-2024 09:53: AM PDT		PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.				
Catalog	Item	Availability	Manufacturer	Mfg. Part #	NDC#	Your Price	Unit
350-97804-EA	Control Company Digital Humidity / Temperature / Dew Point Meter - 1 ea	Sign In	Control Company	4800			EA