

Corning LSE Compact Centrifuge

Description • The Corning LSE Compact Centrifuge is a space saving centrifuge

- Three angle rotors are available for use with the Corning LSE Compact Centrifuge, which can accommodate tube sizes of 15 mL, 50 mL, and 1.5/2.0 mL microcentrifuge tubes
- The LSE Compact Centrifuge will also accommodate a swing-out rotor for 6 x 5 mL tubes
- Optional adapters accommodate other various tube sizes including standard conical tubes and round bottom tubes
- The LSE Compact Centrifuge has a maximum g-force of 4,185 x g
- Other features include an electronic lid lock system, over speed protection, and an automatic shut off imbalance detection system
- The LSE Compact centrifuge is cold room compatible
- Rotors are sold separately.



Specifications:

- Capacity: 12 x 15 mL or 6 x 50 mL rotor
- Maximum speed: 6,000 rpm / 4,185 x g
- Accepts both conical and round bottom tubes
- Space saving footprint

Image(s) are representative of the product group and not necessarily the individual product.

Order	29-Apr-2024 03:59: AM PDT		PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.				
Catalog	Item	Availability	Manufacturer	Mfg. Part #	NDC#	Your Price	Unit
488-10064-EA	LSE Compact Centrifuge, 120V - 1 ea	Sign In	Corning	6755			EA