

Benchmark Scientific IsoBlock Digital Dry Bath



- Description** • Benchmark's IsoBlock dry bath is ideal for incubation of samples at two different temperatures, in a single compact unit
- The two chambers are separated by an insulated wall and are controlled independently, allowing IsoBlock to serve as two dry baths in one
 - The hinged (and removable) lid is also designed with a dividing wall
 - When closed, this dividing wall acts as a barrier, preventing air transfer between chambers
 - The control panel features large digital displays of both time and temperature
 - Both settings of a block can be adjusted at any point, without affecting the settings of the other block
 - The timer function is non-mandatory; IsoBlock can be used for continuous heating
 - Various blocks are available for accommodating nearly all popular tube sizes
 - In addition, the unique Quick-Flip universal blocks accept tubes from 0.5 to 2.0 mL and, with just a quick flip to the other side, they also accommodate 0.2 mL tubes or PCR strips
 - Blocks not included

Specifications:

- Temperature Range: Ambient +5° to 105°C
- Temperature Accuracy: +0.3°C
- Temperature Uniformity: +/- 0.2°C
- Temperature Increments: 0.1°C
- Timer: Off or 1 min. to 99 hr 59 min.
- Dimensions: 6.3 x 14.5 x 5 in. (16 x 36.5 x 13 cm)
- Weight: 8 lbs (4 kg)
- Warranty: 2 years
- Electrical: 120V, 50-60 Hz

Image(s) are representative of the product group and not necessarily the individual product.

Order	28-Apr-2024 00:01: AM PDT		PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.				
Catalog	Item	Availability	Manufacturer	Mfg. Part #	NDC#	Your Price	Unit
385-10313-EA	IsoBlock Digital Dry Bath, with two independently controlled chambers, without blocks, 115V - 1 ea	Sign In	Benchmark Scientific	BSH6000			EA