

BioClean-D Non-Sterile Overboots

Description • Constructed from antistatic low-linting CleanTough material

- Slip-resistant sole
- Tie fastenings for quick and easy donning
- Elasticized opening for a firm fit
- Silicone-free

Specifications:

- Material: Anti-static BioClean-D CleanTough white material & polyurethane sole
- Color: White
- Construction: Bound seams with single needle stitching
- Classification: PPE Cat 3 Type PB 6
- Characteristics: Anti-static to EN1149-5[†] & low particulating
- Compatibility: ISO Class 4
- Packaging: 30 pieces per sealed inner PE bag; one inner bag per sealed outer PE bag; five outer bags per lined carton (150 pieces)

Quality Standards:

• Manufactured in a facility holding ISO 9001:2015 and (EU)2016/425 Module D certifications

- Conforms to Category 3 Personal Protective Equipment PPE Regulation (EU)2016/425
- Tested against standard EN ISO 13034:2005+A1:2009 protective clothing against liquid chemicals (Type PB6)
- Tested against standard EN ISO 14325 protective clothing against chemicals
- Tested against standards: EN 1149-5:2008, protective clothing electrostatic properties; EN 530, Abrasion resistance; EN 7854, Flex cracking resistance; EN 6530, Resistance to penetration by liquids; EN 13934-1, Tensile strength; EN 9073-4, Trapezoidal tear resistance; EN 863, Puncture resistance; and EN 13935-2, Seam strength
- Tested against permeation standard ASTM F739-12
- Processed in an NEBB certified ISO Class 4 environment

[†]NOTE: BioClean CleanTough material is static dissipative and, with a charge half decay time of 0.07 sec, BDOB are ideal for use in a static-safe environment. However the BDOB should not be relied upon to earth the wearer.

Image(s) are representative of the product group and not necessarily the individual product.

Order	28-Apr-2024 14:42: PM PDT	PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.					
Catalog	Item	Availability	Manufacturer	Mfg. Part #	NDC#	Your Price	Unit
206-25520- CS	BioClean-D Non-Sterile Overboots - 150 ea	<u>Sign In</u>	Ansell	BDOB			CS

