

## Corning PYREX Large Desiccator



**Description** • These 10.5 L PYREX desiccators have rugged 24/29 Standard Taper external

sleeves with tooled hose connections that serves as the stopcock

- They are designed so that its manipulation is not affected by the vacuum

- The open position is indicated by the molded arrow on the cap

- A quarter turn from this position closes the desiccator

- For ease in use and improved performance, it is recommended that the Standard Taper sleeve be lubricated with a silicone-based vacuum grease

- The tubulation O.D. is approximately 10 mm

- Bowl capacity is 10500 mL

- Warning: Do not heat or subject to pressure

- Rated 1-atmosphere vacuum

Image(s) are representative of the product group and not necessarily the individual product.

Order	29-Apr-2024 12:20: PM PDT		PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.				
Catalog	Item	Availability	Manufacturer	Mfg. Part #	NDC#	Your Price	Unit
988-31564-EA	PYREX 10.5 L Large Top Desiccator with 24/29 Standard Taper Stopcock - 1 ea Capacity (L): 10.5 Dessicator Style: Vacuum Height (mm): 325 Recommended Plate Dia. (mm): 230 I.D. of Ground Flange (mm): 250 Chamber Depth (mm): 130	<a href="#">Sign In</a>	Corning	3121-250			EA
988-31600-CS	PYREX Replacement Cover for 10.5 L Large Top Desiccator with 24/29 Standard Taper Stopcock, 250 mm - 1 ea		Corning	3121-250CO			CS
988-31603-CS	PYREX Replacement 24/29 Stopcock with Hose Connector - 1 ea		Corning	3121-STPK			CS